



NEW!

AVIATION DEGREASERS



Specially engineered aviation degreasers with strong grease removal of hydraulic fluid, fuel oils, lubricating oils and greases, and other organic residues. They are fast evaporating, quick penetrating, and ideal for cleaning aviation parts.

Contact your Techspray representative for more information or call 800-858-4043.

1647-165 2851-205

- Strong cleaners for removing hydraulic and lubricating fluids
- Nonflammable, fast-drying and leaves no residue
- Do not contain n-propyl bromide
- Compliant with Boeing Spec D6-17487 Rev. T



www.techspray.com

8125 Cobb Center Dr. Kennesaw, GA 30152

678-819-1408 | 800-858-4043

tsales@techspray.com



PWR-4™ Aviation Degreaser

2851-20S 20 oz. Aerosol Can
12 cans/case



- Strong cleaner for removing hydraulic and lubricating fluids
- Powerful spray to clean hard-to-reach parts from as far as 10'
- Nonflammable, fast-drying and leaves no residue
- Does not contain n-propyl bromide
- Compliant with Airbus UK ABR9-0140 General Purpose Cleaning Solvent
- Compliant with Boeing Spec D6-17487 Rev. T:
 - Sandwich corrosion test
 - Paint softening test
 - Hydrogen embrittlement test
 - Stress crazing test

Call-out: FedEx CPN 0311737

PROPERTIES

Flashpoint (method)	none (TAG CC)
GHS flammability	nonflammable
NFPA storage rating	Level 1
Density	1.29 g/ml @20°C
Dielectric breakdown (ASTM D-877)	13.7 kV (liquid)
VOC – EPA	65%
VOC – CARB (classification)	No cap (single purpose degreaser)
VOC – SCAQMD	820g/l
ODP	0%
GWP	437

PLASTICS COMPATIBILITY

HDPE, LDPE, Nylon 6, Nylon 6/6, Phenolic, Polypropylene, POM, PVC, Teflon	Excellent
ABS, Lexan, PMMA / Plexiglas, Polystyrene	Not Compatible

CLEANING PERFORMANCE

Effective on the following soils:

Tests based on modified version of MIL-PRF 29608 (AS) (2008)

- Lubrizol Corrosion Inhibitor
- Unilube All Purpose Grease
- 5W30 synthetic oil
- Fire resistant hydraulic fluid
- Chain lubricant
- Silicone fluid

Aviation Degreaser II

1647-16S 16 oz. Aerosol Can
12 cans/case



- Strong cleaner for removing hydraulic and lubricating fluids
- Nonflammable, fast-drying and leaves no residue
- Does not contain n-propyl bromide
- Compliant with NESHAP 63.741-753
- Compliant with Boeing Spec D6-17487 Rev. T:
 - Sandwich corrosion test
 - Paint softening test
 - Hydrogen embrittlement test
 - Stress crazing test

PROPERTIES

Flashpoint (method)	none (TAG CC)
GHS flammability	nonflammable
NFPA storage rating	Level 1
Density	1.29 g/ml @20°C
Dielectric breakdown (ASTM D-877)	11.9 kV
VOC & SCAQMD – EPA	12.6%
VOC – CARB (classification)	No cap (single purpose degreaser)
ODP	0%
GWP	1300

PLASTICS COMPATIBILITY

ABS, HDPE, Nylon 6, Nylon 6/6, Phenolic, Polypropylene, Polystyrene, POM, PVC, Teflon	Excellent
LDPE	Good
Lexan	Excellent (<i>unstressed</i>), Fair (<i>stressed</i>)
PMMA / Plexiglas	Excellent (<i>unstressed</i>), Fair (<i>stressed</i>)

CLEANING PERFORMANCE

Effective on the following soils:

Tests based on modified version of MIL-PRF 29608 (AS) (2008)

- Castrol Aero 40
- Aeroshell Grease #5 & #33
- Dow Corning 111 Silicone Grease
- Krytox 240AC Aerospace Grease (MIL-PRF 27617 Type III)
- GE F-50 Silicone Oil
- Silicone Damping Fluid (meets VV-D-1078)
- BP Turbo Oil #2197
- Mobil Grease #28
- Skydrol LD4 Fluid
- Royco 782 Hydraulic Fluid (meets MIL-H-83282)
- Lubrizol Alox 165L (meets MIL-C-81309)
- Lockguard 9075 (meets MIL-C-81309)